productinformation

tesa[®] 51036 PET cloth tape for high abrasion protection

tesa® 51036 is a PET cloth wire harness tape with an advanced acrylic adhesive "AAA".

Major Features:

- Flag resistant
- High temperature resistance 150°C/3000h
- High abrasion resistance

Colors: Available in black

Main Application

tesa® 51036 is designed for the engine compartment, providing high abrasion protection.

Technical Data

:	Backing material Total thickness	PET cloth 260 μm	•	Temperature resistance (3000h)	150 °C 302 °F
:	Type of adhesive Adhesion to steel	10.2 mils advanced acrylic 5 N/cm 45.7 oz/in		Abrasion resistance (10mm mandrel) Abrasion resistance (5mm mandrel)	Class D (acc. to LV312) Class D (acc. to LV312)
•	Elongation at break Tensile strength	40 % 275 N/cm 157 lbs/in		Flame resistance as composite Unwind force (roll width > 9mm)	Class B (acc. to LV312) 11 N/roll (30 m/min)
•	Temperature resistance min.	-40 °C -40 °F		Noise damping (decibel)	Class A (acc. to LV312)

Additional Information

- Technical data acc. to LV 312
- Applicable for red ring assembly aid

For latest information on this product please visit http://l.tesa.com/?ip=51036

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

